

rayence

1417WCE

Optimized for
Urgent Care

Free 1 Year Cloud
PACS Access

WRAP Drop
Protection Program



AcuDetect

A next generation Automatic Exposure Detection technology: AcuDetect redefines reliability, which minimizes imaging time and radiation exposure.



16hours



5.2lbs



Water & Dust Resistant



Slip & Impact Protection

Dealer Information:





16 Hours Battery Life

Best in class 16 hour dual batteries offer the convenience of hot-swapping for uninterrupted usage. 10min charge from 0% provides a substantial 40 minutes of operational time.



Light weight

The portable detector allows for more precise movement and enhances security during interactions with the detector.



Slip & Impact Protection

Integrating aerospace grade slip prevention and bumper system to prevent and protect against impact damage, provide tackiness to prevent slip, and is resistant against corrosive elements.



IP 67 Water & Dust Resistance

Enhanced Resistance prevents liquid penetration and is designed to shield against dust and contaminants.

AcuDetect

Meet the next generation of X-ray automatic exposure detection with our AcuDetect technology. Our state-of-the-art silicon-based sensors are designed to detect individual photons, ensuring accurate and dependable identification of X-rays that have been exposed. Detectors equipped with AcuDetect reliably recognize X-ray doses, even for patients weighing nearly 300 pounds or low dose levels.



WRAP Protection

WRAP (Warranty Replacement Accident Program) is an accidental damage replacement program included with Rayence DR Panels. The protection program offers a quick and easy permanent replacement panel for the damaged panel at a low cost during the 5 years of WRAP protection coverage.

Specification

Parameter	1417WCE
Sensor Type	a-si TFT
Scintillator Type	Direct Deposit CsI
Pixel Pitch (µm)	140
AcuDetect	Yes
MultiPixel	-
Glass Free	-
Battery Operating Time (hrs)	Max 16
Weight (w/out battery)	5.2 lbs
Data Transfer	GigE 802.11a/g/n/ac
Energy Range (kVp)	40 - 150
A/D Conversion (bits)	16
Total Pixel Matrix (Pixels)	2500 x 3052
Dimension (mm)	384 x 460 x 15

*Specifications and programs are subject to change without notice